



Gran Gusto Tech



Rotating Plate



Power Boost



3 Way Pay



Easy Dry V2

Atlante Evo 700

Description

Here is the new Saeco Evo line. As a result of the collaboration with the designer Giuliano Galeazzi, this successful line of hot machines has a completely new design, with aluminium inlays, modern and emotional graphics and a new colour display.

Atlante Evo, the most performing freestanding hot machine in the category, evolves and renews its look; its performance is enhanced thanks to the innovative Gran Gusto technology (in the 7 gr Espresso version), that brews a true Italian espresso with only 6 gr of ground coffee. The LED lighting system helps reduce power consumption.

Thanks to its large capacity (up to 700 cups), wide range of beverages (up to 60 different products) and the considerable time-saving in maintenance operations, due to the Saeco Rotating Plate system, Atlante Evo 700 is perfect for medium- and large-sized supply requirements.

This vending machine is the perfect choice for a coffee corner in any venue, whether in the stand-alone version or in combination with the Aliseo Evo freestanding snack&food machine. With the appropriate kit, this machine can be turned into a Master version, in conjunction with the Aliseo Evo Slave. Available in the Espresso with double grinder and double boiler, Espresso with single grinder and double boiler and Instant versions.

Atlante Evo 700: Heart of Coffee.

Accessories

- Independent water tank kit
- Mixer kit for tea replacement with soluble mixer
- Hot water solenoid valve kit
- Memory key to copy and quickly transfer machine settings
- USB key kit
- Eva-Dts kit
- Atlante Evo Master transformation kit

Main features

- Brewing unit with Gran Gusto System + Gran Gusto 6 grams kit (7 gr Espresso version)
- Gran Gusto hydraulics
- New silk-printed images for the upper and lower panels
- LED lighting system
- Generous container capacity
- Easy cleaning and maintenance thanks to the new Saeco Rotating Plate system
- Easily customisable backlit front panels
- User-friendly interface with colour graphic LCD display and easy-to-read and illuminated mechanical buttons
- Versatile dispensing area allowing cups with sizes up to 20 oz (592 ml)
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- New powder dispensing system Saeco Easy Dry V2
- Water filter for preventing the formation of limestone
- The machine is designed for easy use even by persons with disabilities

User interface

- Direct access 20-button keypad for beverage selection
- 2 preselection keys: +/-sugar and 2 settable keys (decaffeinated/barley, no-cup and only-cup options)
- Colour graphic LCD display

Technical data	Atlante Evo 700 Espresso single grinder and double boiler	Atlante Evo 700 Espresso double grinder and double boiler	Atlante Evo 700 Instant
Structural specifications			
Dimensions (w x h x d)	750 x 1830 x 865 mm	750 x 1830 x 865 mm	750 x 1830 x 865 mm
Weight	189 kg	192 kg	168 kg
Electrical specifications			
Power supply	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz
Power consumption	2300 W	2300 W	2300 W
Water specifications			
Boiler	2	2	1
Espresso boiler	brass (600 cc)	brass (600 cc)	
Instant boiler	stainless steel (4,5 l)	stainless steel (4,5 l)	stainless steel (4,5 l)
Water connections			
Water connection	3/4" (1 – 8 bar)	3/4" (1 – 8 bar)	3/4" (1 – 8 bar)
Water supply	standard: water supply optional: independent water tank kit	standard: water supply optional: independent water tank kit	standard: water supply optional: independent water tank kit
Independent water tank	2 tanks of 20 l	2 tanks of 20 l	2 tanks of 20 l
Other specifications			
Cups (h 70 mm)	700	700	700
Cups type ø	70 or 73 mm	70 or 73 mm	70 or 73 mm
Stirrers	550	550	550
Available stirrers	90 – 105 – 115 mm	90 – 105 – 115 mm	90 – 105 – 115 mm
Coffee bean container	1	2	
Instant product container	6	5	7
Sugar container	1	1	1
Number of selections	20	20	20
Number of preselections	2	2	2
Disc mixer	4	4	5
Spiral mixer	1	1	1
Brewing unit	7 gr (Gran Gusto system) or 9 gr	7 gr (Gran Gusto system) or 9 gr	
Canisters capacity			
Coffee beans	1 x 4.2 kg	2 x 3.5 kg	
Instant coffee	1.2 kg	1.2 kg	1.2 kg
Milk	1.3 kg	1.3 kg	1.3 kg
Chocolate	3.5 kg	3.5 kg	3.5 kg
Tea	4.0 kg	4.0 kg	4.0 kg
Sugar	4.5 kg	4.5 kg	3.0 kg

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact approved resin
- Saeco Rotating Plate system
- Rielda lock
- Refill signal for water, coffee and cups
- Adjustable stirrer dispenser
- Electronically controlled boilers temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Illuminated keypad, logo and promotional images
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Built-in utility outlet
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- Safety and anti-boiling thermostats for instant boiler
- CE and VDE approved



Aliseo Evo
+
Atlante Evo 700



Aliseo Evo Slave
+
Atlante Evo 700

Saeco Vending S.p.A. - Località Casona, 1066 - 40041 Gaggio Montano, Bologna - Italy - Tel.: +39 0534 7741 - Fax: +39 0534 774808
info.saecovending.saecoitaly@philips.com - www.saecovending.com

In accordance with its policy of progressive product design Saeco Vending reserves the right to alter specifications.