FD7BT

JOG

Freezer-GN2/1-AISI 304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 1 door. Temperature ranges: -20/-10°C.Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



(€

| 1. 6 | |
|--------------------------------|-----|
| Refrigeration power at -30°C W | 453 |
| | |

General information

| cheral information | | |
|-----------------------------|-------------------|--|
| Supplier/producer 's name | SAGI | |
| Series | Freezy Prime | |
| Supplier's model identifier | FD7BT | |
| Category | vertical cabinet | |
| Type | freezer | |
| Line | catering - GN 2/1 | |

Technical features

| chnical features | |
|--------------------------------|--|
| Temperature ranges, °C | -20/-10 |
| Energy Efficiency Class | D |
| Energy consumption, kWh/24h | 6,5 |
| Energy consumption/year, kWh/a | 2373 |
| Method for energy consumption | EN 22041 |
| Energy Efficiency Index | 62,96 |
| Net usable volume, It | 466 |
| Volume, gross, lt | 590 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$ |
| Refrigerant/GWP | R290/3 |
| Refrigerant charge, kg | 0,1 |
| LWA dB(A) | 40 |

Freezer-GN2/1-AISI 304-Freezy Prime





FD7BT



| Cooling system | ventilated refrigeration system |
|-------------------------------|---|
| Defrosting | automatic |
| Evaporation of condense drain | automatic |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,55 |
| Construction features | |
| Structure | one - piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel (door inner side and inner ceiling made of special anti-fingerprint steel) |
| Insulation thickness, mm | 75 |
| Door | 1 door in AISI 304 stainless steel |
| Standard hinging door | on the right/reversible on the site with self-closing device for openings inferior to 90° |
| Door handle | integrated full-height |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 21/60 |
| Evaporator | positioned outside the compartment |
| Easymaintenance | accessibility to all the functional and control components via a retractable front panel |
| Safety interlock switch | yes, to stop internal fan and switch on compartment light |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 115 ÷ 165 |
| Control and functions | |
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |
| Standard | |
| Key-lock | yes |
| Lighting | yes |
| Couple of guides (n.) | 12 plastic - coated hooks |
| Shelves (n.) | 3, plastic coated |
| Shelf's dimensions, cm | 53x65 (GN 2/1) |
| Shelf loading capacity, kg | 35 |
| Dimensions and weights | |
| Packing (LxDxH), cm | 79x85,5x213 |
| Dimensions (LxDxH), cm | 75x80x204 |
| Gross Weight (kg) | 135 |
| Net Weight (kg) | 120 |

