

## **TECHNICAL DATA SHEET**

| NAME                               | REFERENCE |
|------------------------------------|-----------|
| ULTRA FAST HAND DRYER "AVE" IN ABS | AA19000   |
| DESCRIPTION                        |           |
|                                    |           |

MADE OF HIGH DENSITY WHITE ABS AND POLICARBONATE

OPTICAL SENSOR OPERATED: AUTOMATIC START AND STOP

APPROX DRYING TIME: 10 SEC / SPEED = 400 KM/H

CLASS II: GROUNDING WIRE NOT REQUIRED, CAN BE INSTALED AT 0,6 mts FROM WATER POINT

LINEAL NOZZLE, INTEGRATED IN THE BOTTOM PART

DUST FILTER INCORPOARATED



8427950352164

| CHARACTERISTICS           |  |                                 |   |  |            |  |  |
|---------------------------|--|---------------------------------|---|--|------------|--|--|
| NET                       | DIMENSIONS (mm)                        |                                 | HEIGHT: 330   | WIDTH: 265                                       | DEPTH: 170 |  |  |
| (without packaging)       | WEIGHT (Kg)                            |                                 | 3,195   |  |            |  |  |
| GROSS<br>(with packaging) | DIMENSIONS (mm)                        |                                 | HEIGHT: 375   | WIDTH: 340                                       | DEPTH: 220 |  |  |
|                           | WEGHT(Kg)                              |                                 | 3,990   |  |            |  |  |
| MATE                      | RIALS                                  | ABS PLASTIC CO<br>INTERNAL COMI | PLASTIC COVER<br>RNAL COMPONENTS MADE OF ABS & PC                           |  |            |  |  |
| COLOUR                    | JR / FINISH BODY : WHITE NOZZLE : BLUE |                                 |   |  |            |  |  |
| ELECTRICAL FEATURES       |  | VOLTAGE: 220-240 V              |   | AIRSPEED: 400 Km/HOUR                            |            |  |  |
|                           |  | FREQUENCY: 50 - 60 Hz.          |   | EFFECTIVE AIRFLOW: 220 m³/HOUR                   |            |  |  |
|                           |  | CONSUMPTION: 6,1 Amp.           |   | SOUND PRESSURE: 75 dB                            |            |  |  |
|                           |  | MOTOR POWER: 750 W.             |   | AIR TEMPERATURE: 40 °C (at a distance of 10 cm.) |            |  |  |
|                           |  | RESISTOR POWER: 650 W.          |   | ELECTRICAL INSULATION: CLASS II                  |            |  |  |
|                           |  | TOTAL POWER: 1400 W.            |   | CERTIFICATIONS: CE                               |            |  |  |
|                           |  | MOTOR RPM: 23000                |   | PROTECTION RATIO: IP23                           |            |  |  |
| SPECIFIC                  | ATIONS                                 | 10 SECONDS HAND DRYING TIME     |   |  |            |  |  |
| PACKA                     | .GING                                  |                                 | Approved by: Quality Control Dept  SINGLE UNIT PACKAGING  DATAA: 30/08/2019 |  |            |  |  |