



TOPAZ

- Fusione in lega di alluminio anodizzato.
 - Basamento piano per una facile pulizia.
 - Silenzioso e robusto motore asincrono.
 - Trasmissione con robusta cinghia poliV.
 - Lama forgiata e temprata a forte spessore.
 - Scorrimento carrello su boccole autolubrificanti.
 - Affilatoio incorporato in fusione con doppio smeriglio di serie dal modello 220 A.I. in su.
 - Disponibili lame teflonate o dentate.
 - Inclinazione lama 25°.
- Anodized cast aluminum alloy.
 - Flat base for easy cleaning.
 - Strong and silent-running asynchronous motor.
 - Reliable poliV belt drive.
 - Forged, hardened large thickness blades.
 - Carriage running on self-lubricating bushes.
 - Cast-in sharpener is standard for all models bigger than 220 A.I.
 - Teflon coated or toothed blades are available on demand.
 - 25° blade inclination.



TOPAZ 250-275






Paramano
Hand guard



Protezione inferiore
Bottom shield



Affilatoio scorporato 195-220
Without built-in sharpener 195-220



	mm-inch	watt-Hp	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm	kg	
Topaz 195	195/8"	110/0,15	13	162	185x165	310	220	375	355	300	385	360	370	140	110	135	120	10.5	430x400x370	12
Topaz 220	220/9"	145/0,20	13	245	200x220	380	250	440	410	330	550	400	450	200	130	145	140	13	600x500x420	15
Topaz 220 A.I.	220/9"	145/0,20	13	245	200x220	380	250	440	410	350	550	400	450	200	140	160	155	13.5	600x500x420	15.5
Topaz 250C	250/10"	145/0,20	13	240	230x230	380	250	480	410	360	500	410	475	185	165	180	180	14	600x500x420	16
Topaz 250	250/10"	145/0,20	13	235	220x225	412	255	480	410	360	515	455	505	210	170	190	180	15.5	600x500x420	17.5
Topaz 275	275/11"	145/0,20	13	235	220x225	412	255	520	410	370	525	455	505	200	190	205	205	16.5	600x500x500	19



Topaz 195 - 220



Topaz 220 A.I. - 250