

DS51M

BLAST CHILLER/FREEZER 20/12 kgs. AIR-COOLED



RANGE FEATURES

- Exterior: AISI 304 18-10 stainless steel front, side and top panels.
Interior: AISI 304 18-10 stainless steel.
- Satin scotchbrite finish on door, side panels, control panel and top.
- CE Mark.



FUNCTIONAL FEATURES

- Worktop in 18-10 stainless steel with rounded satin front edge.
- One-piece construction with rounded internal corners.
CFC-free expanded polyurethane insulation, 55 mm thickness, density 38kg/ m³.
- Hinged fan cover panel for easy access to the evaporator and fan during cleaning.
- Diamond-polished inner floor for improved hygiene. Drain outlet for easy cleaning of interior.
- Useful for 1/1 GN and 40 x 60 cm. containers.
- Removable wire rack in AISI 304 stainless steel wire, 5 positions, 60 mm. vertical spacing intervals.
- Control panel with electronic single-point circuit board. LCD display, available in multilanguage version, to activate automatically the storage phase at end of cycle.
- Self-closing door. Full height outer stainless steel handle.
- Depth with door open 1375 mm. Easily-removable magnetic gasket.
Door frame heating element.
- Inner dimensions mm 620(L)x595(P)x375(H). Interior capacity 100 litres (as per EN 28187).
- Plastic defrost drip tray on outer base.
- Stainless steel feet with plastic heat-resistant pads, height-adjustable from 103 to 135 mm.

TECHNICAL FEATURES

- Cooling unit at evaporation temperature -25°C and condensation temperature 53,5°C rated at 813 Watt with hermetic compressor. Refrigerant gas: R404A. Air cooling.
- Production per cycle: 20 kg from +90° C to +3°C in 90 minutes and 12 kg of product from +90°C to -18°C in 240 minutes. Tropicalized at 32°C (climate class N or 4 ISO441).
- Evaporation temperature control with thermostat valve. Internal operation: ventilated cell, ventilation not directly on foods. Copper/aluminium rustproofed evaporator.
Manual defrosting.
- All controls and parts accessible from front of appliance.

Width	Cm	74,5		
Depth	Cm	70	Electric Power	kW 1,35
Height	Cm	90		
Net weight	Kg	115	Standard connection	V-Hz 230V 1N~ / 50Hz